

SPECIFICATIONS

Model	WAT-902H2 ULTIMATE (EIA)	WAT-902H2 ULTIMATE (CCIR)
Pick-up element	1/2" interline transfer CCD image sensor	
Number of total pixels	811(H) × 508(V)	795(H) × 596(V)
Number of effective pixels	768(H) × 494(V)	752(H) × 582(V)
Unit cell size	8.4um(H) × 9.8um(V)	8.6um(H) × 8.3um(V)
Shutter speeds	EI1: 1/60 sec. - 1/100000 sec. EI2: 1/100 sec. - 1/100000 sec. FL: 1/100 sec. OFF: 1/60 sec.	EI1: 1/50 sec. - 1/100000 sec. EI2: 1/120 sec. - 1/100000 sec. FL: 1/120 sec. FL: 1/50 sec.
	1/250, 1/500, 1/1000, 1/2000, 1/5000, 1/10000, 1/100000 sec.	
Minimum illumination	0.0001 lx. F1.4	

Model	WAT-902H3 ULTIMATE (EIA)	WAT-902H3 ULTIMATE (CCIR)
Pick-up element	1/3" interline transfer CCD image sensor	
Number of total pixels	811(H) × 508(V)	795(H) × 596(V)
Number of effective pixels	768(H) × 494(V)	752(H) × 582(V)
Unit cell size	6.35um(H) × 7.40um(V)	6.50um(H) × 6.25um(V)
Shutter speeds	EI1: 1/60 sec. - 1/100000 sec. EI2: 1/100 sec. - 1/100000 sec. FL: 1/100 sec. OFF: 1/60 sec.	EI: 1/50 sec. - 1/100,000 sec. EI2: 1/120 sec. - 1/100000 sec. FL: 1/120 sec. FL: 1/50 sec.
	1/250, 1/500, 1/1000, 1/2000, 1/5000, 1/10000, 1/100000 sec.	
Minimum illumination	0.0002 lx. F1.4	

Common specifications	
Synchronizing system	Internal sync.
Video output	1Vp-p, 75ohms, unbalanced
Resolution (H)	570TVL (Center)
SN ratio	More than 50dB (AGC OFF)
AGC	①HI: 5-60dB ②LO: 5-32dB ③MGC(5-60dB)
Back light compensation	①OFF(Default) ②Center ③Lower ④Center + lower
Gamma correction	①HI ($\gamma \doteq 0.35$) ②LO ($\gamma \doteq 0.45$) ③OFF ($\gamma \doteq 1$)
Power supply	DC12V±10%
Power consumption	1.32W (110mA)
Operating temperature	-10°C - +40°C
Storage temperature	-30°C - +70°C
Dimensions(W×H×L)	35.5 × 40 × 63 (mm)
Weight	approx. 98g

Design and specifications are subject to change without notice.

DIMENSIONS (mm)

